

安徽艾约塔硅油有限公司

IOTA CORPORATION LTD.

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158

Fax: 86-552-3822922

TECHNOLOGY MAKES LIFE BETTER

安徽省蚌埠市高新区兴中路 985 号日月科技园

电话: 86-552-3827158

传真: 86-552-3822922

IOTA 888A Silicone Sealant for Solar Modules

Features

- 1.UL, TUV, CE certified
- 2.Excellent resistance to UV radiation
- 3.Stable and flexible from -50°C to +180°C
- 4. Excellent electrical insulation performance
- 5. Protects from mechanical shocks and chemical mediators
- 6.Excellent weatherability and ozone resistance
- 7.Excellent watertight seal property
- 8. Sufficient protection of wafers from contamination or oxidation
- 9. Non-toxic , non-corrosive

COLOURS

IOTA 888A is available in white, black and other customized colours

PACKAGING

IOTA 888A is available in disposable cartridges (net 310ml), or sausages (net 600ml), or drums (net 188L, about250kg)

Typical properties

These values are not intended for use in preparing specifications.

Test Method	Property		Unit	Result
GB/T 13477	Appearance		fine paste	
GB/T 13477 (ISO 7390)	Slump		mm	0
GB/T 13477 (ASTM D	Tack free time		min.	12
2377)				
GB/T 13477 (ISO 7619)	Hardness		Shore A	50
GB/T 528 (ISO 37)	Tensile	Initial strength	MPa	2.1
	strength	85℃,85% RH,1000h	MPa	1.4
GB/T 528 (ISO 37)	Elongation	Initial strength	%	360
	at break	85℃,85% RH,1000h	%	360
GB/T 7124 (ISO 4587)	Shear strength		MPa	1.15
GB/T 1695 (ASTM D 149)	Dielectric break down strength		kV/mm	20.5
GB/T 1692	Volume resistivity		Ω·cm	1×10 ¹⁵
GB/T 2048	Fire resistance rate		94HB	
Cure time, 3mm		h	24	



安徽艾约塔硅油有限公司

IOTA CORPORATION LTD.

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158

Fax: 86-552-3822922

安徽省蚌埠市高新区兴中路 985 号

日月科技园

电话: 86-552-3827158

传真: 86-552-3822922

*GB: Chinese National Standard

ASTM: American Society for Testing and Materials ISO: International Standardization Organization

The "GB" testing method is equivalent or partly equivalent to that in the "()

STORAGE AND SHELF LIFE

IOTA 888A should be stored in original unopened containers over the temperature from 4°C to 27°C. It has a shelf life of 12 months from the date of manufacture. IOTA 888A is solvent free, non-hazardous for transportation.

HOW TO USE

Apply a bead of IOTA 888A to one of the prepared surfaces, then quickly cover with the other substrate be bonded and remove the excess sealant

Tool immediately before a skin forms

A plug of used material may form in the tip of a tube or cartridge during storage. This is easily removed and does not affect the remaining contents.

Air pressure should be maintained at $0.2 \sim 0.4$ MPa when using pneumatic gun.

IOTA CORPORATION LTD.

Add: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

TeL: 0086-552-7183958 Fax: 0086-552-3822922

Whatsapp: 0086-15556181299 WeChat: Amandalin99

QQ: 309136222

Email: sales02@siliconeoil.net
Website: www.rtvsilicone.net