

## 安徽艾约塔硅油有限公司

## IOTA CORPORATION LTD.

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158

Fax: 86-552-3822922

# 安徽省蚌埠市高新区兴中路 985 号

日月科技园

电话: 86-552-3827158

传真: 86-552-3822922

### Extra Soft Cellular Silicone IOTA-BF-1000

Compressibility, softness, and durability allow BF-1000 to adapt to various environments, making it an ideal choice for sealing outdoor enclosures, protecting electronics from shock and heat, and providing cushioning or vibration isolation for various applications.

#### **Features and Benefits**

Excellent memory and low stress relaxation reduces maintenance costs associated with gasket failures due to compression set and softening.

Softness allows designers to use less force to seal enclosures and still protect their device from the environment.

High compressibility allows the material to conform to variable width gaps and awkward shapes, thereby allowing engineers more design flexibility.

Resistance to ultraviolet light, ozone, extreme temperatures, and flame enables consistent performance in all environments.

Available through distribution sites throughout North America, Europe, and Asia.

FDA compliant in accordance with FDA Regulation 21 CFR 177.2600. ‡

### **Applications**

Environmental seals to protect against penetration of dust, moisture, air or light within outdoor enclosures such as lighting fixtures, and electronic cabinets.

Vibration isolation in electronic components and transportation vehicles.

Fire retardant thermal insulation.

### Installation

Available with a pressure-sensitive adhesive on one or two sides to allow easy application to a variety of surfaces.

	IOTA-BF-1000				
Property	Test Method	Typical Value			
	PHYSICAL	•			



# 安徽艾约塔硅油有限公司

# IOTA CORPORATION LTD.

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158

Fax: 86-552-3822922

## TECHNOLOGY MAKES LIFE BETTER

安徽省蚌埠市高新区兴中路 985 号 日月科技园

电话: 86-552-3827158 传真: 86-552-3822922

Color		White, Gray & Black
Thickness, mm (inches)		1.60 – 25.40 (0.063 – 1.000)
Standard Width, mm (inches)		914 (36)
Density, kg/m³ (lb./ft³)	ASTM D 1056	208 (13)
Compression Force	Force measured @	
Compression Force	25% Deflection	20.7 (3)
Deflection, kPa (psi)	ASTM D 1056	
	ASTM D 1056	
	Test D @ 70°C (158°F),	< 1
Compression Cat	22 hrs.	< 1
Compression Set,	ASTM D 1056	
% max.	Test D @ 100°C	< 5
	(212°F), 22 hrs.	< 5
Tensile Strength, kPa (psi)	ASTM D 412	241 (35)
Elongation, %	ASTM D 412	90
	FLAMMABILITY & OUTGAS	SING
Flame Resistance	UL 94	Listed V-0 and HF-1
Flame Spread Index (L s )	ASTM E 162	< 35
	ASTM E 662	
Smoke Density (D s )	Tested @ 4.0 minutes	< 50
	Tested @ 1.5 minutes	< 20



### TECHNOLOGY MAKES LIFE BETTER

安徽省蚌埠市高新区兴中路 985 号

日月科技园

电话: 86-552-3827158

传真: 86-552-3822922

# 安徽艾约塔硅油有限公司

## IOTA CORPORATION LTD.

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158

Fax: 86-552-3822922

Toxic Gas Emissions	SMP-800C & BSS 7239	Pass
Rating		

The information contained in this Data Sheet is intended to assist you in designing with IOTA Silicone Materials. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown on the Data Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of IOTA Silicone Materials for each application.